



CALDERA-T6

Order No.: 1000295

PRODUCTINFOS

- B-stock items -

Pair of active studio and recording speakers, 2 x 100 W

- 2-way active circuit per speaker system with separate power amplifiers for subwoofer and tweeter (bi-amping)
- Amplifier power rating bass: 30 W, treble: 25 W
- Maximum output power total: 100 W
- Bass-reflex MDF cabinet, laminated surface
- 16 cm bass-midrange speaker with green polypropylene cone and 25 mm soft dome tweeter
- Each speaker system is equipped with a balanced XLR input and jack input (6.3 mm), all with gain control
- Volume control
- Ideally suited as studio monitor speakers for recording, audio/video presentations and home hi-fi

TECHNICAL SPECIFICATIONS

CALDERA-T6

Active/passive	active
Transmission technology	cable
Total output power	100 W
Power rating (RMS)	55 W
Frequency range	50-20,000 Hz
Input signal	1,500 mV/32 kΩ (bal.)
System	2-way bass-reflex
Bass speaker	16 cm bass speaker
Tweeter	25 mm soft dome tweeter
Number of speakers	2
Speaker size	16 cm
SPL	89 dB/W/m
Max. rated SPL	105 dB
Radiation angle/beam angle	H: 120°/V: 100°
Radiation angle, horizontal	120°
Radiation angle, vertical	100°
Housing material	MDF wood
Colour	black
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/110 VA
Dimensions	210 x 320 x 255 mm
Width	210 mm
Height	320 mm
Depth	255 mm
Weight	6.5 kg
Inputs	1 x XLR, bal., IN (each speaker system) 1 x 6.3 mm jack, bal., IN (each speaker system)
Other features	pair
Packing dimensions (W x H x L)	0.36 x 0.41 x 0.63 m
Gross weight	14.5 kg
Net weight	13 kg