



# 10/2





# **DRIVE-10A**

Order No.: 1000193

## **PRODUCTINFOS**

#### With the DRIVE series

you will get robust and easy-to-use PA speakers which are suitable for versatile applications and feature the latest DSP-controlled amplifier technology. There are 3 selectable presets available to provide a perfect sound adjustment for any kind of application. These robust and high-quality cabinets made of birch plywood are suitable for general use. The arrangement of the handles allow for easy manageability.

## Professional active DSP speaker system with 2-channel amplifier, 200 W

- Compact 10/2 full range system with cabinet made of birch plywood
- DSP-controlled 2-channel amplifier (bass: class D, tweeter: class A/B)
- 3 selectable presets
- FLAT (linear adjustment)
- MUSIC (slightly raised bass and treble)
- LOW CUT (with high-pass filter for application with an additional subwoofer)
- 25 cm (10") bass speaker and 25 mm (1") horn tweeter, can be turned by 90°



- Excellent sound characteristics
- High-quality coating and neat workmanship
- Multi-purpose positioning and installation options
- · Horn tweeter with consistent radiation pattern
- M8 threaded inserts for suspended installation, stand sleeve
- Volume control
- 2 x balanced line in
- 2 x parallel line out
- 1 x balanced mix out
- Power and clip indicator

## **TECHNICAL SPECIFICATIONS**

#### **DRIVE-10A**

Active/passive active
Transmission technology cable
Total output power 400 W

DSP-controlled 200 W (140 + 60)

Power rating (RMS) bass: 140 W

treble: 60 W

Frequency range 55-20,000 Hz

Input signal 790 mV/40 k $\Omega$  (line, bal.)

System 10/2 full range

Bass speaker 25 cm (10") bass speaker

Tweeter 25 mm (1") horn tweeter

Number of speakers 2

 Speaker size
 25 cm (10")

 SPL
 98 dB/W/m

 Max. rated SPL
 123 dB

Radiation angle/beam angle H: 90°/V: 60°, horn can be turned

Radiation angle, horizontal 90° Radiation angle, vertical 60°

Housing material birch plywood

Colour black

Mounting device M8 threaded inserts, stand sleeve

Admiss. ambient temp. 0-40 °C

Power supply ~ 230 V/50 Hz/350 VA Dimensions 320 x 530 x 350 mm

Width 320 mm



## **DRIVE-10A**

Height 530 mm

Depth 350 mm

Weight 12.18 kg

Inputs 1 x comb. XLR/6.3 mm: line

1 x XLR: line

Outputs 2 x XLR par. out

1 x XLR mix out

Other features DSP-controlled limiter

3 selectable presets

Packing dimensions (W x H x L)  $0.42 \times 0.63 \times 0.45 \text{ m}$ 

Gross weight 16.02 kg
Net weight 12.18 kg