



DRIVE-15A

Order No.: 1000195

PRODUCTINFOS

With the DRIVE series

you will get robust and easy-to-use PA speakers which are suitable for versatile applications and feature the latest DSP-controlled amplifier technology. There are 3 selectable presets available to provide a perfect sound adjustment for any kind of application. These robust and high-quality cabinets made of birch plywood are suitable for general use. The arrangement of the handles allow for easy manageability.

Professional active DSP speaker system with 2-channel amplifier, 360 W

- Compact 15/2 full range system with cabinet made of birch plywood
- DSP-controlled 2-channel amplifier (bass: class D, tweeter: class A/B)
- 3 selectable presets

- FLAT (linear adjustment)
- MUSIC (slightly raised bass and treble)
- LOW CUT (with high-pass filter for application with an additional subwoofer)

- 38 cm (15") bass speaker and 25 mm (1") horn tweeter, can be turned by 90°

- Excellent sound characteristics
- High-quality coating and neat workmanship
- Multi-purpose positioning and installation options
- Horn tweeter with consistent radiation pattern
- M8 threaded inserts for suspended installation, stand sleeve
- Volume control
- 2 x balanced line in
- 2 x parallel line out
- 1 x balanced mix out
- Power and clip indicator

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

TECHNICAL SPECIFICATIONS

DRIVE-15A

Active/passive	active
Transmission technology	cable
Total output power	750 W
Power rating (RMS)	DSP-controlled 360 W (300 + 60) bass: 300 W treble: 60 W
Frequency range	40-20,000 Hz
Input signal	790 mV/40 kΩ (line, bal.)
System	15/2 full range
Bass speaker	38 cm (15") bass speaker
Tweeter	25 mm (1") horn tweeter
Number of speakers	2
Speaker size	38 cm (15")
SPL	98 dB/W/m
Max. rated SPL	125 dB
Radiation angle/beam angle	H: 90°/V: 60°, horn can be turned
Radiation angle, horizontal	90°

DRIVE-15A

Radiation angle, vertical	60°
Housing material	birch plywood
Colour	black
Mounting device	M8 threaded inserts, stand sleeve
Admiss. ambient temp.	0-40 °C
Power supply	~ 230 V/50 Hz/550 VA
Dimensions	415 x 695 x 455 mm
Width	415 mm
Height	695 mm
Depth	455 mm
Weight	22.04 kg
Inputs	1 x comb. XLR/6.3 mm: line 1 x XLR: line
Outputs	2 x XLR par. out 1 x XLR mix out
Other features	DSP-controlled limiter 3 selectable presets
Packaging dimensions (W x H x L)	0.56 x 0.81 x 0.52 m
Gross weight	28.07 kg
Net weight	22.04 kg

DRIVE-15A

EAN code	4007754276282
Net weight	22.04 kg