



SKYROCK/POWER

Order No.: 1001007

PRODUCTINFOS

Portable PA speaker system,

with integrated Bluetooth receiver.

- Operation via mains connection or integrated rechargeable lead gel battery 12 V/18 Ah (operating time at moderate volume: up to 40 hours, operating time at full volume: up to 10 hours), with LED for indicating charging status
- Bluetooth receiver (version 5.0) for wireless connection of portable audio players
- Bluetooth TWS feature (True Wireless Stereo) for linking 2 x PA speaker system SKYROCK to a stereo speaker system
- High-performance class D version 120 W
- 2-way speaker system with 38 cm (15") bass speaker and 25.4 mm (1") horn tweeter
- 1 adjustable microphone input via comb. jack (XLR/6.3 mm)
- 1 adjustable aux input (3.5 mm jack)
- Adjustable reverb via microphone input
- USB charging port for portable audio players

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Zum Falsch 36
28307 Bremen
Germany
info@monacor.com

Warning and Safety Instructions

The device is supplied with dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Risk of electric shock!

Do not use this device and disconnect it immediately from the power supply if the device or the power supply cable is visibly damaged, if a defect might have occurred after the device was dropped or suffered a similar accident, if malfunctions occur. Any repairs must be carried out by specialists.

The product is suitable for indoor use only. Protect it against dripping water, splash water and high air humidity (admissible ambient temperature range is 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated in the device must be dissipated by air circulation. Never cover the air vents of the housing.

If the device is to be put out of operation definitely, dispose of the product in accordance with local regulations.

Never put (rechargeable) batteries in the household waste. Always dispose of the batteries in accordance with local regulations.

TECHNICAL SPECIFICATIONS

SKYROCK/POWER

Rated power (P_{RMS})	55 W (bass)
	21 W (treble)
Peak output power	130 W
Frequency range	38-20,000 Hz
Inputs	12 mV/1 k Ω (Mic),
	70 mV/3 k Ω (Aux)
Max. SPL	129 dB
Power supply	~ 100-240 V/50-60 Hz/120 VA, or rech. batt. 12 V/18 Ah (WP18-12SHR)
Admiss. ambient temp.	0-40 °C
Dimensions	470 x 815 x 365 mm
Weight	29.2 kg
Connections	1 x XLR/6.3 mm jack (mic),
	1 x 3.5 mm jack (aux)
	1 x USB Type-A

SKYROCK/POWER

EAN code 4007754422931

Net weight 29.16 kg