



DRIVE-10P



Order No.: 1000198

PRODUCTINFOS

With the passive speaker systems of the DRIVE series,

you will get robust and easy-to-use PA speakers which are suitable for versatile applications. These robust and high-quality cabinets made of birch plywood are suitable for general use. The arrangement of the handles allow for easy manageability.

Professional PA speaker system, 400 W

- Compact 10/2 full range system with cabinet made of birch plywood
- 25 cm (10") bass speaker and 25 mm (1") horn tweeter, can be turned by 90°
- Protective circuit for the tweeter
- Excellent sound characteristics
- High-quality coating and neat workmanship
- Multi-purpose positioning and installation options
- Horn tweeter with consistent radiation pattern
- M8 threaded inserts for suspended installation
- 2 x SPEAKER terminal IN/OUT
- Stand sleeve



TECHNICAL SPECIFICATIONS

| DRIVE-10P | |
|-----------|--|
|-----------|--|

| Active/passive | passive |
|---|---|
| | |
| Transmission technology | cable |
| Total power rating | 400 W |
| Power rating (RMS) | 200 W |
| Impedance | 8 Ω |
| Frequency range | 55-20,000 Hz |
| System | 10/2 full range |
| Bass speaker | 25 cm (10") bass speaker |
| Tweeter | 25 mm (1") horn tweeter |
| Number of speakers | 2 |
| Speaker size | 25 cm (10") |
| SPL | 98 dB/W/m |
| Max. rated SPL | 123 dB |
| Radiation angle/beam angle | H: 90°/V: 60°, horn can be turned |
| Radiation angle, horizontal | 90° |
| | |
| Radiation angle, vertical | 60° |
| Radiation angle, vertical Housing material | 60° birch plywood |
| - | |
| Housing material | birch plywood |
| Housing material Colour | birch plywood black |
| Housing material Colour Mounting device | birch plywood black M8 threaded inserts, stand sleeve |
| Housing material Colour Mounting device Admiss. ambient temp. | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width Height | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm 530 mm |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width Height Depth | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm 530 mm 350 mm |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width Height Depth Weight | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm 530 mm 350 mm 11.25 kg |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width Height Depth Weight Inputs | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm 530 mm 350 mm 11.25 kg 1 x SPEAKER jack |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width Height Depth Weight Inputs Outputs | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm 350 mm 11.25 kg 1 x SPEAKER jack 1 x SPEAKER jack par. out |
| Housing material Colour Mounting device Admiss. ambient temp. Dimensions Width Height Depth Weight Inputs Outputs Packing dimensions (W x H x L) | birch plywood black M8 threaded inserts, stand sleeve 0-40 °C 320 x 530 x 350 mm 320 mm 530 mm 11.25 kg 1 x SPEAKER jack 1 x SPEAKER jack par. out 0.46 x 0.65 x 0.43 m |