



DRIVE-12P

Order No.: 1000197

PRODUCTINFOS

With the passive speaker systems of the DRIVE series,

you will get robust and easy-to-use PA speakers which are suitable for versatile applications. These robust and high-quality cabinets made of birch plywood are suitable for general use. The arrangement of the handles allow for easy manageability.

Professional PA speaker system, 500 W

- Compact 12/2 full range system with cabinet made of birch plywood
- 30 cm (12") bass speaker and 25 mm (1") horn tweeter, can be turned by 90°
- Protective circuit for the tweeter
- Excellent sound characteristics
- High-quality coating and neat workmanship
- Multi-purpose positioning and installation options
- Horn tweeter with consistent radiation pattern
- M8 threaded inserts for suspended installation
- 2 x SPEAKER terminal IN/OUT
- Stand sleeve

TECHNICAL SPECIFICATIONS

DRIVE-12P

Active/passive	passive
Transmission technology	cable
Total power rating	500 W
Power rating (RMS)	250 W
Impedance	8 Ω
Frequency range	45-20,000 Hz
System	12/2 full range
Bass speaker	30 cm (12") bass speaker
Tweeter	25 mm (1") horn tweeter
Number of speakers	2
Speaker size	30 cm (12")
SPL	98 dB/W/m
Max. rated SPL	123 dB
Radiation angle/beam angle	H: 90°/V: 60°, horn can be turned
Radiation angle, horizontal	90°
Radiation angle, vertical	60°
Housing material	birch plywood
Colour	black
Mounting device	M8 threaded inserts, stand sleeve
Admiss. ambient temp.	0-40 °C
Dimensions	360 x 620 x 380 mm
Width	360 mm
Height	620 mm
Depth	380 mm
Weight	15.9 kg
Inputs	1 x SPEAKER jack
Outputs	1 x SPEAKER jack par. out
Packing dimensions (W x H x L)	0.49 x 0.77 x 0.47 m
Gross weight	20.52 kg
Net weight	15.9 kg