



MX-2IO

Order No.: 0203170

PRODUCTINFOS

2-channel USB recording interface

- Integrated USB audio interface (will be identified and addressed as an external sound card)
- Full-duplex USB port (allows for simultaneous recording and reproduction) for reproduction of digital audio data from a PC and for recording mixings onto a PC
- 2 mono input channels with XLR input (mic) and 6.3 mm input (switchable mic/line)
- Selectable 20 dB attenuation and LED level display
- Input channels switchable mono/stereo
- 1 additional stereo input
- 1 x 6.3 mm jack output L/R
- 1 x 3.5 mm jack stereo output
- Adjustable headphone output
- +48 V phantom power, can be activated as required for each channel
- Stereo LED level display
- Robust metal housing of compact size

delamar.de

“An easy-to-connect USB audio interface with two inputs and outputs each. Despite its compact size, the MX-2IO from IMG STAGELINE impresses with versatile input and output options. Any kind of microphone,

instrument or audio player can be fed in and [...] be recorded. The LED chains for indicating the level of every path are quite unique in this class. Layout, haptics and neat workmanship are impressive. Last but not least, both the sound and output power of the headphone amplifier are absolutely perfect. Despite the missing monitor mixing option of the analogue input and DAW signals, it is a really neat little interface.”

SOUNDCHECK 06/2019

“The small and compact box fits into any laptop backpack. In combination with suitable microphones, it thus provides a professional high-quality solution for mobile recording.

The highly flexible inputs and preamplifiers allow for general use, from weak microphone signals, instrument signals to strong line signals. This is particularly interesting for home recording.

Thanks to versatile features, good sound characteristics and a very attractive price, the MX-2IO is surely going to become a permanent companion for musicians and studio operators.”

TECHNICAL SPECIFICATIONS

MX-2IO

No. of channels	2
No. of inputs	5
Mic input	2.5 mV, 2 x 3-pole XLR
Line input	45 mV, 1 x 6.3 mm jack 11 k Ω (line)/460 k Ω (inst.)
Aux input	1.25 V, 1 x 3.5 mm jack
Master output	500 mV, 2 x 6.3 mm jack L/R
Aux output	500 mV, 1 x 3.5 mm jack
Headphones	$\geq 16 \Omega$, 1 x 3.5 mm jack
USB	yes
Frequency range	20-20,000 Hz
THD	$\leq 0.03\%$
Crosstalk	92 dB
Phantom power	+48 V
Power supply	via USB interface DC 5 V/500 mA
Operating voltage (possible alternative)	DC 5 V
Power supply (possible alternative)	500 mA
Admiss. ambient temp.	0-40 °C
Width	160 mm
Height	50 mm
Depth	110 mm
Weight	634 g

MX-210

Packing dimensions (W x H x L) 0.155 x 0.075 x 0.27 m

Gross weight 0.854 kg

Net weight 0.7 kg